

## **SPECIFICATIONS**

|                         | 420        | 415        | 390        |
|-------------------------|------------|------------|------------|
| Full lenght             | 4.20 m     | 4.15 m     | 3.90 m     |
| Full lenght             | 2.93 m     | 2.89 m     | 2.72 m     |
| Width                   | 1.87 m     | 1.87 m     | 1.86 m     |
| Interior width          | 0.89 m     | 0.89 m     | 0.86 m     |
| Depth                   | 1.00 m     | 1.00 m     | 1.00 m     |
| Tube diameter           | 50 cm      | 50 cm      | 45 cm      |
| Air chambers            | 4          | 3          | 3          |
| Weight                  | 128 kg     | 89 kg      | 69 kg      |
| Tube inflation pressure | 0.25 bar   | 0.25 bar   | 0.25 bar   |
| Passengers              | 8          | 8          | 7          |
| Maxiumum power          | 60 HP      | 25 HP      | 25 HP      |
| Engine shaft            | Simple L   | Simple L   | Simple L   |
| Design category         | С          | С          | С          |
| PVC Black               | 5 390€ TTC | 3 665€ TTC | 3 455€ TTC |
| PVC Grey                | 5 390€ TTC | 3 665€ TTC | 3 455€ TTC |
| Hypalon Grey            | 8 390€ TTC | 6 080€ TTC | 5 660€ TTC |
|                         |            |            |            |



## **EQUIPMENT**

## STANDARD

Anti-corrosion treatment of the aluminum hull Marine powder paint

Bow roller

Lifting and towing chainplates integrated to the hull

UV-resistant marine EVA pad coating

Ultra wide anti-drag strip

Bow guard

Double grips

Aluminum bench on slide rail

Pump, oars and repair kit

Dimensional and weight tolerances ±10%

In tropical climates, the use of 3D TENDER PVC boats is excluded from the warranty. Prices and specifications are subject to change without notice.