

SPECIFICATIONS

	290	270	250	230	200	180	160
Full lenght	2.90 m	2.70 m	2.50 m	2.30 m	2.00 m	1.80 m	2.00 m
Full lenght	2.34 m	2.15 m	1.95 m	1.77 m	1.45 m	1.26 m	1.06 m
Width	1.36 m	1.35 m	1.35 m	1.34 m	1.31 m	1.29 m	1.29 m
Interior width	0.67 m	0.67 m	0.67 m	0.66 m	0.63 m	0.62 m	0.61 m
Tube diameter	34-40 cm	34-40 cm	34-40 cm	32-36 cm	32-35 cm	32-35 cm	30 cm
Air chambers	3	3	3	3	3	2	2
Weight	20.3 kg	18.9 kg	17.4 kg	16.6 kg	14.3 kg	12.9 kg	11.5 kg
Floor inflation pressure	0.80 bar						
Pression tube	0.25 bar						
Passengers	4	4	3	2	2	2	1
Maximum load weight	510 kg	484 kg	450 kg	350 kg	250 kg	200 kg	180 kg
Maximum power	6 HP	6 HP	6 HP	4 HP	4 HP	4 HP	3 HP
Engine shaft	Simple S						
Sac dimensions	98x48 x28cm	98x48 x28cm	98x48 x28cm	98x45 x28cm	98x45 x28cm	90x45 x28cm	90x48 x26cm
PVC Grey / Black	1 355€ TTC	1 313€ TTC	1208€ TTC	1040€ TTC	998€ TTC	935€ TTC	893€ TTC
PVC Grey / White	1 355€ TTC	1 313€ TTC	1208€ TTC	1040€ TTC	998€ TTC	935€ TTC	893€ TTC

EQUIPMENT

STANDARD

PVC Valmex® Mehler tube
High pressure honeycomb floor
Adjustable aluminum bench on
slide
Grips
Inflator
Repair kit
Oars
Transport backpack





Dimensional and weight tolerances ±10%

In tropical climates, the use of 3D TENDER PVC boats is excluded from the warranty. Prices and specifications are subject to change without notice.